



STANDARD FINISHES
Black, White, & Silver



UP TO 133 lm/W PERFORMANCE

DIRECT LIGHT	WATTS PER FOOT
375 lm/ft	3.10
500 lm/ft	4.03
750 lm/ft	5.73
1000 lm/ft	7.48
1250 lm/ft	9.73

Performance based on 4-foot luminaire at 4,000K @ 25-degrees C

LIGHT LOSS FACTOR

CCT	CRI	%
4000K	84+	100%
3500K	84+	97.1%
3000K	84+	95.7%
2700K	84+	94.1%
4000K	92+	88.9%
3500K	92+	85.5%
3000K	92+	83.8%
2700K	92+	82.4%

ORDER GUIDE

ARX.4-R [] [] [] [] [] [] [] [] [] []

EXAMPLE

ARX.4-R	FT	500	4	35K	B	UNV	S1	W	
---------	----	-----	---	-----	---	-----	----	---	--

OPTIONS

[] J (Multiple Selections)

A. MODEL	B. TRIM	C. DISTRIBUTION	D. LENGTH	E. COLOR TEMPERATURE
ARX.4-R	FT Flange Trim G1 Grid 15/16" G9 Grid 9/16" GS Grid Slot TL Trimless Spackle Flange	375 375 lm/ft 500 500 lm/ft 750 750 lm/ft 1000 1000 lm/ft 1250 1250 lm/ft XXX Custom lm/ft	2 2 ft (24 in) 3 3 ft (36 in) 4 4 ft (48 in) 5 5 ft (60 in) 6 6 ft (72 in) 7 7 ft (84 in) 8 8 ft (96 in) XXX System Run	27K 2700K 30K 3000K 35K 3500K 40K 4000K

NOTES

		Consult factory for outputs between min and max.	
--	--	--	--

F. CRI	G. VOLTAGE	H. DRIVER	I. FINISH
8 80+CRI 9 90+CRI	UNV 120-277v 347 347v	S1 1% Dimming (0-10v) LDE1 Lutron Hi-Lume 1% ELO Fade to Black DXL 0.1% EldoLED 1% Dexas	DALI DALI 2.0 Compatible W White B Black S Silver CC Custom Colors

90 CRI option has an R9 value greater than 60.	347 may not be available in all configurations.	AWN-R, AWNR-B, VDO, VRF, SPD, & CLM options supplied with DXL driver standard.	Consult factory for custom colors.
--	---	--	------------------------------------

OPTIONS

J. CONTROLS & FACTORY OPTIONS			
Q NONE	Leave Blank	SPD Osram SensiLUM Daylight/Harvest/Occ	Q EB Emergency Battery (10-Watt)
Q AWNR-W	Lutron Athena Wire-less Node (RF-only) in White	CLM Osram Connecting Light Module (CLM)	Q EC Emergency Circuit Night Light Circuit
Q AWNR-B	Lutron Athena Wire-less Node (RF-only) in Black	DOC Enlighted Daylight/Harvesting Occ (SU-5E-01)	NL Chicago Plenum
Q VDO	Lutron Vive (RF/Daylight/Occ)		
Q VRF	Lutron Vive RF Fixture Control		

AWN-R, AWNR-B, VDO, VRF, SPD, & CLM options supplied with DXL driver standard.
EB option only available for lengths 4ft or greater.
May choose more than one option in this category.

LIGHT SOURCE

Long life name brand LED chips and boards to ensure the highest of quality while providing even and smooth illumination throughout our luminaires.

Our luminaires are available in 2700K, 3000K, 3500K and 4000K color temperature.

Optional 80CRI or 90CRI available in all CCT options.

LUMEN MAINTENANCE

The projected lumen maintenance of the name brand mid-powered LED's are projected to maintain 80% (L80) of their initial output for +80,000 hours.

CONSTRUCTION

The housings are constructed of (6063T5) extruded aluminum. Our internal joiner system is designed to the highest of standards to ensure our precision cut housings align and fit tightly without light leak. Our precision fitting end caps are constructed out of die cast aluminum and our steel reflectors are painted white.

FINISH

Polyester powder, low gloss textured paint finish applied after a multi-stage pretreatment. Standard luminaire finishes include white, silver, and black. Custom color options are available. (Consult Factory).

OPTICS

Indirect curved reflector system.

DRIVERS

All of our luminaires come standard with 1% dimming and THD <20% utilizing 0-10v constant current protocol. 120v/277v is standard with the option of 347v. Driver ambient operating temperature -30°C to +50°C.

EMERGENCY

An integral factory installed 10 watt emergency battery pack. Emergency circuit and Night Light circuit options are available.

LUMINAIRE LENGTH

Our ARX.4 Recessed luminaire series are available in 2', 3', 4', 5', 6', 7' and 8' individual lengths or continuous row configurations. Continuous row configurations are joined together on-site utilizing the joiner kits provided.



CONTINUOUS RUN ORDER GUIDES

Please use the following run guides for fixture ordering. If your product will require a submittal, our in-house Application Engineering Team will work closely with you on your project.

ALUMINUM PRODUCT ORDER GUIDE	
RUN LENGTH (ft)	RUN CONFIGURATION - SECTION LENGTHS
9	6' + 3'
10	6' + 4'
11	6' + 5'
12	6' + 6'
13	6' + 7'
14	8' + 6'
15	8' + 7'
16	8' + 8'
17	6' + 5' + 6'
18	6' + 6' + 6'
19	6' + 7' + 6'
20	8' + 4' + 8'
21	8' + 5' + 8'
22	8' + 6' + 8'
23	8' + 7' + 8'
24	8' + 8' + 8'
25	5' + 8' + 8' + 4'
26	4' + 6' + 6' + 6' + 4'
27	6' + 8' + 8' + 5'
28	6' + 8' + 8' + 6'
29	7' + 8' + 8' + 6'

*Standard Run Configurations Shown, Consult Factory for Custom Configurations.

ALUMINUM PRODUCT ORDER GUIDE	
RUN LENGTH (ft)	RUN CONFIGURATION - SECTION LENGTHS
30	6' + 6' + 6' + 6' + 6'
31	6' + 6' + 7' + 6' + 6'
32	8' + 8' + 8' + 8'
33	5' + 8' + 8' + 8' + 4'
34	6' + 8' + 8' + 8' + 4'
35	6' + 8' + 8' + 8' + 5'
36	6' + 8' + 8' + 8' + 6'
37	8' + 8' + 5' + 8' + 8'
38	8' + 8' + 6' + 8' + 8'
39	8' + 8' + 7' + 8' + 8'
40	8' + 8' + 8' + 8' + 8'
41	5' + 8' + 8' + 8' + 8' + 4'
42	6' + 8' + 8' + 8' + 8' + 4'
43	6' + 8' + 8' + 8' + 8' + 5'
44	6' + 8' + 8' + 8' + 8' + 6'
45	7' + 8' + 8' + 8' + 8' + 6'
46	3' + 8' + 8' + 8' + 8' + 8' + 3'
47	4' + 8' + 8' + 8' + 8' + 8' + 3'
48	8' + 8' + 8' + 8' + 8' + 8'
49	5' + 8' + 8' + 8' + 8' + 8' + 4'
50	6' + 8' + 8' + 8' + 8' + 8' + 4'

*Standard Run Configurations Shown, Consult Factory for Custom Configurations.

