





UP TO 128 lm/W PERFORMANCE				
DIRECT LIGHT	375 lm/ft	500 lm/ft	750 lm/ft	1000 lm/ft
375 lm/ft	6.15	7.10	9.03	11.60
500 lm/ft	6.85	7.80	9.73	12.30
750 lm/ft	9.00	9.95	11.88	14.45
1000 lm/ft	11.50	12.45	14.38	16.95

Performance based on 4-foot luminaire at 4,000K @ 25-degrees C



STANDARD FINISHES
Black, White, & Silver



LUX | ENABLED

**LIGHT LOSS FACTOR**

CCT	CRI	%
4000K	84+	100%
3500K	84+	97.1%
3000K	84+	95.7%
2700K	84+	94.1%
4000K	92+	88.9%
3500K	92+	85.5%
3000K	92+	83.8%
2700K	92+	82.4%

ORDER GUIDE

LUX-W-DI												
A	B	C	D	E	F	G	H	I	J	K	L	
LUX-W-DI	LAM	500	BAT	500	8	40K	8	2	UNV	S1	W	

EXAMPLE

OPTIONS

M, N (Multiple Selections)



Suitable for damp locations.

A. MODEL	B. DIRECT OPTICS	C. DIRECT DISTRIBUTION	D. INDIRECT OPTICS	E. INDIRECT DISTRIBUTION	F. LENGTH	G. COLOR TEMPERATURE
Q LUX-W-DI	Q LAM Lambertian	Q 375 375 lm/ft Q 500 500 lm/ft Q 750 750 lm/ft Q 1000 1000 lm/ft XXX Custom lm/ft	Q LAM Lambertian Q BAT Bat Wing	Q 375 375 lm/ft Q 500 500 lm/ft Q 750 750 lm/ft Q 1000 1000 lm/ft XXX Custom lm/ft	Q 3 3 ft (36 in) Q 4 4 ft (48 in) Q 5 5 ft (60 in) Q 6 6 ft (72 in) Q 7 7 ft (84 in) Q 8 8 ft (96 in) XXX System Run	Q 27K 2700K Q 30K 3000K Q 35K 3500K Q 40K 4000K WCT White Color Tuning 2700K - 6500K

NOTES

Consult factory for outputs between min and max.	Consult factory for outputs between min and max.	Fixture lengths are only available in one foot increments. Refer to Pattern configuration guide below for nomenclature. Please see Pattern Guide on p.2 for further details.	WCT - max lm/ft is 1000 based on 80 CRI and 4000K. Other CCT's are available consult factory.
--------------------------------------------------	--------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------

H. CRI	I. CIRCUIT	J. VOLTAGE	K. DRIVER			
Q 8 9	80+CRI 90+CRI	Q 1 Q 2 1 - Circuit 2 - Circuit	Q UNV 347 120-277v 347v	Q S1 LDE1 1% Dimming (0-10v) Lutron Hi-Lume 1% Fade to Black 0.1% EldoLED 1% Dexal	DXL2 DALI PSQ	Dexal 2-Channel DALI 2.0 Compatible Lutron T Series

90 CRI option has an R9 value greater than 60.	347 may not be available in all configurations.	AWNR-W, AWNR-B, VDO, VRF, SPD, & CLM options supplied with DXL driver standard.
------------------------------------------------	-------------------------------------------------	---------------------------------------------------------------------------------

OPTIONS

L. FINISH	M. CONTROLS & FACTORY OPTIONS	N. QUICKSHIP		
Q W Q B Q S CC White Black Silver Custom Colors	Q NONE Q AWNR-W Leave Blank Lutron Athena Wireless Node (RF-only) in White Q AWNR-B Lutron Athena Wireless Node (RF-only) in Black Q VDO Lutron Vive (RF/Daylight/Occ) Q VRF Lutron Vive RF Fixture Control	SPD Osram SensiLUM Daylight/Harvest/Occ CLM Osram Connecting Light Module (CLM) DAY Wattstopper Daylight Sensor (FD-301) OCC Wattstopper Occ Sensor (FS-205V2) DOC Enlighted Daylight/Harvesting Occ (SU-5E-01)	Q EB Emergency Battery (10-Watt) Q EC Emergency Circuit NL FP Night Light Circuit Flat End Cap	Q QS10 QuickShip 10 - Day (Depletion Policy: Subject to Availability)

Consult factory for custom colors.	AWNR-W, AWNR-B, VDO, VRF, SPD, & CLM options supplied with DXL driver standard. EB option only available for lengths greater than 4ft. Sculpted end caps are standard for this product. May choose more than one option in this category.	Please see note on p.2 for further details regarding QuickShip.
------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------



LIGHT SOURCE

Long life name brand LED chips and boards to ensure the highest of quality while providing even and smooth illumination throughout our luminaires.

Our luminaires are available in 2700K, 3000K, 3500K and 4000K color temperature as well as White Color Tuning (2700-6500K).

Optional 80CRI or 90CRI available in all CCT options.

LUMEN MAINTENANCE

The projected lumen maintenance of the name brand mid-powered LED's are projected to maintain 80% (L80) of their initial output for +80,000 hours.

CONSTRUCTION

The housings are constructed of (6063T5) extruded aluminum. Our internal joiner system is designed to the highest of standards to ensure our precision cut housings align and fit tightly without light leak. Our precision fitting end caps are constructed out of die cast aluminum and our steel reflectors are painted white.

FINISH

Polyester powder, low gloss textured paint finish applied after a multi-stage pretreatment. Standard luminaire finishes include white, silver, and black. Custom color options are available. (Consult Factory).

OPTICS

Snap in extruded frosted acrylic lens

DRIVERS

All of our luminaires come standard with 1% dimming and THD <20% utilizing 0-10v constant current protocol. 120v/277v is standard with the option of 347v. Driver ambient operating temperature -30°C to +50°C.

EMERGENCY

An integral factory installed 10 watt emergency battery pack. Emergency circuit and Night Light circuit options are available.

LUMINAIRE WEIGHT

Our LUX Wall Direct/Indirect luminaire series are available in 3', 4', 5', 6', 7' and 8' individual lengths or continuous row configurations. Continuous row configurations are joined together on-site utilizing the joiner kits provided.

QUICKSHIP

Indicates QuickShip option 10-day lead times.



Up to 500 linear feet or 100 individual luminaires.
Consult Factory for larger projects.

PLEASE NOTE:

- 10-day lead times do not include weekends or holidays.
- A clean order must be received by 12:00 PM EST. All orders received after 12:00 PM EST will be entered the following day.
- Changing orders of any kind will require a new ESD.
- All QuickShip items must be on a separate PO.

CONTINUOUS RUN ORDER GUIDES

Please use the following run guides for fixture ordering. If your product will require a submittal, our in-house Application Engineering Team will work closely with you on your project.

ALUMINUM PRODUCT ORDER GUIDE	
RUN LENGTH (ft)	RUN CONFIGURATION - SECTION LENGTHS
9	6' + 3'
10	6' + 4'
11	6' + 5'
12	6' + 6'
13	6' + 7'
14	8' + 6'
15	8' + 7'
16	8' + 8'
17	6' + 5' + 6'
18	6' + 6' + 6'
19	6' + 7' + 6'
20	8' + 4' + 8'
21	8' + 5' + 8'
22	8' + 6' + 8'
23	8' + 7' + 8'
24	8' + 8' + 8'
25	5' + 8' + 8' + 4'
26	4' + 6' + 6' + 6' + 4'
27	6' + 8' + 8' + 5'
28	6' + 8' + 8' + 6'
29	7' + 8' + 8' + 6'

*Standard Run Configurations Shown, Consult Factory for Custom Configurations.

ALUMINUM PRODUCT ORDER GUIDE	
RUN LENGTH (ft)	RUN CONFIGURATION - SECTION LENGTHS
30	6' + 6' + 6' + 6' + 6'
31	6' + 6' + 7' + 6' + 6'
32	8' + 8' + 8' + 8'
33	5' + 8' + 8' + 8' + 4'
34	6' + 8' + 8' + 8' + 4'
35	6' + 8' + 8' + 8' + 5'
36	6' + 8' + 8' + 8' + 6'
37	8' + 8' + 5' + 8' + 8'
38	8' + 8' + 6' + 8' + 8'
39	8' + 8' + 7' + 8' + 8'
40	8' + 8' + 8' + 8' + 8'
41	5' + 8' + 8' + 8' + 8' + 4'
42	6' + 8' + 8' + 8' + 8' + 4'
43	6' + 8' + 8' + 8' + 8' + 5'
44	6' + 8' + 8' + 8' + 8' + 6'
45	7' + 8' + 8' + 8' + 8' + 6'
46	3' + 8' + 8' + 8' + 8' + 8' + 3'
47	4' + 8' + 8' + 8' + 8' + 8' + 3'
48	8' + 8' + 8' + 8' + 8' + 8'
49	5' + 8' + 8' + 8' + 8' + 8' + 4'
50	6' + 8' + 8' + 8' + 8' + 8' + 4'

*Standard Run Configurations Shown, Consult Factory for Custom Configurations.

