


STANDARD FINISHES
Black, White, & Silver



UP TO 133 lm/W PERFORMANCE	
DIRECT LIGHT	WATTS PER FOOT
375 lm/ft	12.4
500 lm/ft	16.1
750 lm/ft	22.9
1000 lm/ft	29.9
1250 lm/ft	38.9

Performance based on 4-foot luminaire at 4,000K @ 25-degrees C

LIGHT LOSS FACTOR		
CCT	CRI	%
4000K	84+	100%
3500K	84+	97.1%
3000K	84+	95.7%
2700K	84+	94.1%
4000K	92+	88.9%
3500K	92+	85.5%
3000K	92+	83.8%
2700K	92+	82.4%

LUX | **ENABLED**



ORDER GUIDE

ARX.4-S									
A	B	C	D	E	F	G	H	I	

EXAMPLE

ARX.4-S	1000	8	40K	8	UNV	S1	W	9C	
---------	------	---	-----	---	-----	----	---	----	--

OPTIONS

J, K,L (Multiple Selections)

A. MODEL	B. DIRECT DISTRIBUTION			C. LENGTH			D. COLOR TEMPERATURE		E. CRI
ARX.4-S	375	500	375 lm/ft	2	2 ft (24 in)	27K	2700K	8	80+CRI
	750	1000	500 lm/ft	3	3 ft (36 in)	30K	3000K	9	90+CRI
	1250	XXX	750 lm/ft	4	4 ft (48 in)	35K	3500K		
			1000 lm/ft	5	5 ft (60 in)	40K	4000K		
			1250 lm/ft	6	6 ft (72 in)				
			Custom lm/ft	7	7 ft (84 in)				
				8	8 ft (96 in)				
				XXX	System Run				

PQVGU

Consult factory for outputs between min and max.	90 CRI option has an R9 value greater than 60.
--	--

F. VOLTAGE		G. DRIVER				H. FINISH		I. MOUNTING	
UNV	120-277v	S1	1% Dimming (0-10v)	DALI	DALI 2.0 Compatible	W	White	9C	9/16 in Tee Clip
347	347v	LDE1	Lutron Hi-Lume 1% Fade to Black			B	Black	15C	15/16 in Tee Clip
		ELO	0.1% EidoLED			S	Silver	SC	Screw Slot Tee Clip
		DXL	1% Dexas			CC	Custom Colors	HC	Hard Ceiling

347 may not be available in all configurations.	AWN-R-W, AWNR-B, VDO, VRF, SPD, & CLM options supplied with DXL driver standard.	Consult factory for custom colors.
---	--	------------------------------------

OPTIONS

J. CONTROLS & FACTORY OPTIONS

<input type="checkbox"/> NONE	Leave Blank	SPD	Osram SensiLUM Daylight/Harvest/Occ	<input type="checkbox"/> EB	Emergency Battery (10-Watt)
<input type="checkbox"/> AWNR-W	Lutron Athena Wireless Node (RF-only) in White	CLM	Osram Connecting Light Module (CLM)	<input type="checkbox"/> EC	Emergency Circuit
<input type="checkbox"/> AWNR-B	Lutron Athena Wireless Node (RF-only) in Black	DAY	Wattstopper Daylight Sensor (FD-301)	NL	Night Light Circuit
<input type="checkbox"/> VDO	Lutron Vive (RF/Daylight/Occ)	OCC	Wattstopper Occ Sensor (FS-205v2)	FO	Flat Open End Plate
<input type="checkbox"/> VRF	Lutron Vive RF Fixture Control	DOC	Enlighted Daylight/Harvesting Occ (SU-5E-01)	FC	Flat Closed End Plate

AWN-R-W, AWNR-B, VDO, VRF, SPD, & CLM options supplied with DXL driver standard.

EB option only available for lengths 4ft or greater. Sculpted end cap is standard.

May choose more than one option in this category.

LIGHT SOURCE

Long life name brand LED chips and boards to ensure the highest of quality while providing even and smooth illumination throughout our luminaires.

Our luminaires are available in 2700K, 3000K, 3500K and 4000K color temperature.

Optional 80CRI or 90CRI available in all CCT options.

LUMEN MAINTENANCE

The projected lumen maintenance of the name brand mid-powered LED's are projected to maintain 80% (L80) of their initial output for +80,000 hours.

CONSTRUCTION

The housings are constructed of (6063T5) extruded aluminum. Our internal joiner system is designed to the highest of standards to ensure our precision cut housings align and fit tightly without light leak. Our precision fitting end caps are constructed out of die cast aluminum.

FINISH

Polyester powder, low gloss textured paint finish applied after a multi-stage pretreatment. Standard luminaire finishes include white, silver, and black. Custom color options are available. (Consult Factory).

OPTICS

Curved reflector system.

DRIVERS

All of our luminaires come standard with 1% dimming and THD <20% utilizing 0-10v constant current protocol. 120v/277v is standard with the option of 347v. Driver ambient operating temperature -30°C to +50°C.

EMERGENCY

An integral factory installed 10 watt emergency battery pack. Emergency circuit and Night Light circuit options are available.

LUMINAIRE LENGTH

Our ARX.4 Surface Direct luminaire series are available in 2', 3', 4', 5', 6', 7' and 8' individual lengths or continuous row configurations. Continuous row configurations are joined together on-site utilizing the joiner kits provided.



CONTINUOUS RUN ORDER GUIDES

Please use the following run guides for fixture ordering. If your product will require a submittal, our in-house Application Engineering Team will work closely with you on your project.

ALUMINUM PRODUCT ORDER GUIDE	
RUN LENGTH (ft)	RUN CONFIGURATION - SECTION LENGTHS
9	6' + 3'
10	6' + 4'
11	6' + 5'
12	6' + 6'
13	6' + 7'
14	8' + 6'
15	8' + 7'
16	8' + 8'
17	6' + 5' + 6'
18	6' + 6' + 6'
19	6' + 7' + 6'
20	8' + 4' + 8'
21	8' + 5' + 8'
22	8' + 6' + 8'
23	8' + 7' + 8'
24	8' + 8' + 8'
25	5' + 8' + 8' + 4'
26	4' + 6' + 6' + 6' + 4'
27	6' + 8' + 8' + 5'
28	6' + 8' + 8' + 6'
29	7' + 8' + 8' + 6'

*Standard Run Configurations Shown, Consult Factory for Custom Configurations.

ALUMINUM PRODUCT ORDER GUIDE	
RUN LENGTH (ft)	RUN CONFIGURATION - SECTION LENGTHS
30	6' + 6' + 6' + 6' + 6'
31	6' + 6' + 7' + 6' + 6'
32	8' + 8' + 8' + 8'
33	5' + 8' + 8' + 8' + 4'
34	6' + 8' + 8' + 8' + 4'
35	6' + 8' + 8' + 8' + 5'
36	6' + 8' + 8' + 8' + 6'
37	8' + 8' + 5' + 8' + 8'
38	8' + 8' + 6' + 8' + 8'
39	8' + 8' + 7' + 8' + 8'
40	8' + 8' + 8' + 8' + 8'
41	5' + 8' + 8' + 8' + 8' + 4'
42	6' + 8' + 8' + 8' + 8' + 4'
43	6' + 8' + 8' + 8' + 8' + 5'
44	6' + 8' + 8' + 8' + 8' + 6'
45	7' + 8' + 8' + 8' + 8' + 6'
46	3' + 8' + 8' + 8' + 8' + 8' + 3'
47	4' + 8' + 8' + 8' + 8' + 8' + 3'
48	8' + 8' + 8' + 8' + 8' + 8'
49	5' + 8' + 8' + 8' + 8' + 8' + 4'
50	6' + 8' + 8' + 8' + 8' + 8' + 4'

*Standard Run Configurations Shown, Consult Factory for Custom Configurations.

